



SGL106

## Crossover™ ANSI • CSA •



VENTED  
FRAME



INCLUDES  
STRAP

Removable indirect vented rolled rubber gasket // Adjustable detachable strap with quick release // Custom imprinting available



### Black and Gray Frame | 3 Variations

- SBG10610DT ● ● Clear H2X AF
- SBG10620DT ● ● Gray H2X AF
- SBG10680DT ● I/O Mirror AF

### Gray and Lime Frame | 1 Variation

- SGL10610DT ● ● Clear H2X AF

Part No.	Lens Marking	Temple Marking
SBG10610DT	P Z87 + U6	P Z87 + / P c SEI Z94.3
SBG10620DT	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SBG10680DT	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
SGL10610DT	P Z87 + U6	P Z87 + / P c SEI Z94.3

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

### General Specifications

Weight: 32.9 gm  
 PD: 64 mm  
 Bridge: 13.6 mm  
 Lens base: 9 curve  
 Lens size diagonal: 78.6 mm  
 Lens size vertical: 46.8 mm  
 Lens thickness: 2.0 mm  
 Overall length (lens - tip): 170 mm  
 Overall width (hinge - hinge): 130.5 mm  
 Closest point between lens: 9.5 mm  
 Strap Length: 165 - 195 mm

### Materials

Lens: polycarbonate  
 Rubber gasket: polycarbonate & thermoplastic rubbers (TPR)  
 Temples: polycarbonate  
 Temple strap: polyester  
 Hook for temple strap: nylon  
 Takeup loop for strap: nylon



WATCH THE  
**CROSSOVER**  
 VIDEO