



PYRAMEX
Perform At Your Peak

Proximity® ANSI CE CSA



FOAM PADDED
OPTIONS



CO-INJECTED
TEMPLES

Flame resistant foam padding

Ultra lightweight spectacle – 26.3gm

Slim co-injected temples

Part No.	Black Frame
ESB9310ST ●●●	AF Clear H2X
ESB9310STM ●●●	AF Clear H2MAX
ESB9320ST ●●●	AF Gray H2X
ESB9320STM ●●●	AF Gray H2MAX
ESB9330ST ●●●	AF Amber H2X
ESB9380ST ●●●	AF I/O Mirror



vimeo.com/pyramex/h2max



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] (●) and Canadian [CSA Z94.3] (●) standards.

Proximity®

General Specifications

Weight: 26.3 gm
 PD: 64 mm
 Bridge: 16.5 mm
 Lens base: 9.5 curve
 Lens size diagonal: 75.8 mm
 Lens size vertical: 50.4 mm
 Lens thickness: 1.6 mm
 Overall length (lens - tip): 161 mm
 Overall width (hinge - hinge): 135 mm
 Closest point between lens: 14.5 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate & thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Foam gasket: nylon & ethylene-vinyl acetate (EVA) foam

Part No.	Lens Markings	Frame Markings
ESB9310ST	2 C - 1.2 P 1 F N CE	CE P EN166 F
ESB9310STM	2 C - 1.2 P 1 F K N CE	CE P EN166 F
ESB9320ST	5 - 2.5 P 1 F N CE	CE P EN166 F
ESB9320STM	5 - 2.5 P 1 F K N CE	CE P EN166 F
ESB9330ST	2 - 1.2 P 1 F N CE	CE P EN166 F
ESB9380ST	5 - 1.7 P 1 F CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 K: Resistance to surface damage by fine particles
 N: Filter with anti-fog
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact



There's more to see at
PYRAMEXSAFETY.COM

[P] +44 (0) 1635 254220 | [E] info@pyramexeurope.com