

TECHNICAL SPECIFICATION



Powercap® Active™ Filters (PR)

Black / CAU601-001-100



DESCRIPTION

Pair of replacement Powercap® Active™ filters.

*Powercap® Active™ filters meet the requirements of EN 12941 when fitted to Powercap® Active™ respirator.

OPTIONS

Black (CAU601-001-100)

SAFETY STANDARDS

EN 12941



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsspsafety.com / Web: www.jsspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 12 Dec 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.



SPECIFICATIONS

Classification
TH1 (Turbo Hood)

Usage
R (Reusable)



Activated Carbon Layer
No

Maximum Total Inward Leakage (TIL)
10% When Fitted To PowerCap® Active™
Respirator

UK Assigned Protection Factor
10 - When Fitted To Powercap® Active™
Respirator

Filter Casing Material
ABS Plastic



BSI Kitemark
Yes



Filter Type
P (Protects Against Solid and Liquid Aerosols)



(D) Resistance to dust clogging
Yes - Mandatory Test in EN12941

Minimum Filtration Efficiency
90% For P Rated

Nominal Protection Factor
10 - When Fitted To Powercap® Active™
Respirator

Filter Material
Pleated Media

Filter Shelf Life
5 Years



Product Weight
108g Per Pair Including Pre-Filters

FEATURES



Powered Air

Protection to EN 12941 TH1P provides a cooling, comfortable supply of filtered air at 160 litres per minute, eliminating breathing resistance and visor misting.



Bump Cap Head Protection

The cap uses JSP HardCap™ A1+ bump cap technology, exceeding the EN 812 standard. The cap cover is easily removable, wipeable and machine washable.



Micro USB Charging

PowerCap® Active™ is supplied with a micro USB cable for recharging in as little as 5 hours. The PowerBox™1 battery pack features a built-in fuel gauge, making it easy to check charge level.

RANGE



VIDEOS



youtu.be/0yFoliUPusM

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-powercap_active.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 12 Dec 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.

