

Replacement Integrated Shield for EVO® VISTAshield®

Replacement Integrated Shield for EVO® VISTAshield™ / AMV200-000-000



DESCRIPTION

Replacement Integrated Anti Mist Anti Scratch KN Shield for EVO®VISTAshield® Helmet

When fitted to the ${\sf EVO} @VISTAshield \ensuremath{\mathbb{B}}$ Helmet this replacement shield has the following features and benefits -

Optical Class 1 - High optical quality with no optical distortion

K Rated - Anti-Scratch resistance to surface damage from fine particles N Rated - Anti-Mist resistance to fogging

A - Impact Rating. High energy impact; 6mm, 0.86g ball travelling at 425mph (685kph)

UV 2C-1.2 2: UV filter (EN170) provides protection from harmful UV. C: Unimpaired colour perception. 1.2: High light transmission.

OPTIONS

Replacement Integrated Shield for EVO® VISTAshield[™] (AMV200-000-000)

SAFETY STANDARDS

EN 166 • EN 170



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number 2C

Manufacturer's Trademark JSP Dagger



High Energy Impact resists a 6 mm, 0.86g ball @ 190 m/s Maximum protection for face shields A Resistance to Surface Damage by Fine Particles (optional)



Visor Length 12.5cm

Recyclable

Κ



BSI Kitemark

Yes

VIDEOS

www.youtube.com/watch?v=i8-pUrIrl1o



LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2



Optical Class (1 - Class 1 - High quality for regular use. 2 - Class 2 - Medium quality for occasional use. 3 - Class 3 - Low quality for exceptional use)1



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional T



Resistance to fogging (optional)

Material Polycarbonate



Product Weight 103g

DOWNLOADS

Image Pack (ZIP)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.