

PressToCheck[™] P3 Dust Filters

Pack of 2 / BMN990-001-700



DESCRIPTION

PressToCheck[™] is the easiest way to face-fit check the seal of your respirator, every time you put it on! The range features HEPA filtration exceeding 99.97%, Low profile design maximising compatibility and low breathing resistance across the range.

F-4003 P3 dust encapsulated filters, featuring PressToCheck[™] technology for daily face-fit reassurance.

Winner of the BSIF Product Innovation Award.

OPTIONS

Pack of 2 (BMN990-001-700)

SAFETY STANDARDS

EN 143



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



SPECIFICATIONS

No

Classification P3

Usage R (Reusable)



Activated Carbon Layer

Minimum Filtration Efficiency 99.97% To NIOSH Standard For P100 Filter

Maximum Total Inward Leakage (TIL) 0.05% when fitted to a Force10 Full Face Mask

Nominal Protection Factor 1000 When Fitted To A Force10 Full Face Mask

UK Assigned Protection Factor 40 When Fitted To A Force10 Full Face Mask

Latex free Yes

Filter Material **Pleated Media**

Filter Shelf Life 10 Years



Overall Product Weight 92g Per Pair

FEATURES



Increased Product Life

PressToCheck[™] encapsulated filters offer ultimate longevity - the durable design makes the filters easy to clean and reuse. Correct cleaning, maintenance and storage increases the useful life of the product.

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Construction and Infrastructure

VIDEOS

- youtu.be/1Y9G8E9kEXQ (\mathbf{b})
- youtu.be/Ecyu_ftPPX4 (\mathbf{b})
- youtu.be/-oUSyP9 NsA

Manufacturing

DOWNLOADS

- Image Pack (ZIP)
- doc-force-press-to-check-filter-f-4003.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



 ∇

Filter Type

(D) Resistance to dust clogging Yes - mandatory test in EN 143

Minimum Filtration Efficiency 99.95%

Maximum Total Inward Leakage (TIL) 2% when fitted to Force8 Half Mask

Nominal Protection Factor 48 When Fitted To A Force8 Half Mask

UK Assigned Protection Factor 20 When Fitted To A Force8 Half Mask



Туре Press To Check Technology

Metal Free Yes

Filter Casing Material ABS



BSI Kitemark Yes

P (Protects Against Solid and Liquid Aerosols)

