TECHNICAL SPECIFICATION

JSP®

Replacement Jetstream® Dust & Gas Filter TH2A2P R SL

Jetstream® Dust & Gas Filter TH2A2P R SL / CBU620-000-000

A2PSL filter

DESCRIPTION

Replacement TH2A2P R SL filter for Jetstream® GVX Unit .

*Replacement Jetstream® Dust & Gas Filter TH2A2P R SL meets the requirements of EN 12941 when fitted to Jetstream® respirator.

OPTIONS

Jetstream® Dust & Gas Filter TH2A2P R SL (CBU620-000-000)

SAFETY STANDARDS

EN 12941

SINCE 1964 OXFORD, ENGLAND

SPECIFICATIONS

Classification
TH2A2P R SL

Usage
R (Reusable)

Activated Carbon Layer
Yes

Maximum Total Inward Leakage (TIL)
2% When Fitted To Jetstream

UK Assigned Protection Factor
20 When Fitted To JetStream GVX Unit

Filter Material
Pleated Media & Ativated Carbon

Filter Shelf Life
3 Years

Product Weight
TH2A2P R SL Filter 592g

Filter Type
Organic Vapours, Nusance Odours and Particulate

D (D) Resistance to dust clogging
Yes - Mandatory Test In EN12491

Minimum Filtration Efficiency
98%

Nominal Protection Factor
50 When Fitted To JetStream GVX Unit

Metal Free
No

Filter Casing Material
ABS

BSI Kitemark
Yes

RANGE

Jetstream®
ACCESSORIES

DOWNLOADS

Image Pack (ZIP)

doc-jetstream.pdf (PDF)