

# TECHNICAL SPECIFICATION



## PressToCheck™ A2 P3 Filters

Pack of 2 / BMN740-000-600



### DESCRIPTION

PressToCheck™ is the easiest way to face-fit check the seal of your respirator, every time you put it on! The range features HEPA filtration exceeding 99.95%, Low profile design maximising compatibility and low breathing resistance across the range.

F-4123 A2P3 organic gas / vapour + dust replacement encapsulated filters, featuring PressToCheck™ technology for daily face-fit reassurance.

Winner of the BSIF Product Innovation Award.

### OPTIONS

**Pack of 2 (BMN740-000-600)**

### SAFETY STANDARDS

EN 14387



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 16 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Classification  
A2P3

Usage  
R (Reusable)



Activated Carbon Filter  
Yes

Maximum Total Inward Leakage (TIL)  
2% when fitted to Force8 Half Mask

Nominal Protection Factor  
12 When Fitted To A Force8 Half Mask

UK Assigned Protection Factor  
10 When Fitted To A Force8 Half Mask



Type  
Press To Check Technology

Metal Free  
Yes

Filter Casing Material  
ABS



BSI Kitemark  
Yes



Filter Type  
Organic Vapours, Nuisance Odours and Particulate



(D) Resistance to dust clogging  
Yes – D marking = passes optional clogging test

Minimum Filtration Efficiency  
99.95% For P Rated

Maximum Total Inward Leakage (TIL)  
0.05% when fitted to a Force10 Full Face Mask

Nominal Protection Factor  
1000 When Fitted To A Force10 Full Face Mask

UK Assigned Protection Factor  
20 When Fitted To A Force10 Full Face Mask

Latex free  
Yes

Filter Material  
Pleated Media & Activated Carbon

Filter Shelf Life  
10 Years



Product Weight  
231g Per Pair

## FEATURES



### Increased Product Life

PressToCheck™ encapsulated filters offer ultimate longevity – the durable design makes the filters easy to clean and reuse. Correct cleaning, maintenance and storage increases the useful life of the product.

## VIDEOS

- [youtu.be/1Y9G8E9kEXQ](https://youtu.be/1Y9G8E9kEXQ)
- [youtu.be/Ecyu\\_ftPPX4](https://youtu.be/Ecyu_ftPPX4)
- [youtu.be/-oUSyP9\\_NsA](https://youtu.be/-oUSyP9_NsA)

## DOWNLOADS

- [Image Pack \(ZIP\)](#)
- [doc-force-press-to-check-filter-f-4123.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 16 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

